

BGA SDMP 267 form (only for use in the BGA airworthiness system)

Aircraft Maintenance Programme (AMP)					
Aircraft identification					
1	Registration: G-	Type: ASW 15A	Serial no: 15000		
Basis for the maintenance programme					
2	This is the BGA recommended option for owners to declare their aircraft maintenance program. This template is for all ELA1 Sailplanes, Self-Launching/Sustaining sailplanes and TMG, not involved in commercial operations, declaring the "other" Programme complying with M.A.302(i) <input checked="" type="checkbox"/> Note the BGA SDMP 267 lists all the scheduled inspection requirements in tasks 1 to 89 and is equivalent to EASA Appendix A, AMC M.A.302 (e) , required by EASA 'Minimum Inspection Programme'.				
Design approval holder (DAH) maintenance data					
3	Equipment manufacturer and type		Applicable maintenance data reference (at latest revision)		
3a	Aircraft (other than balloons)	Alexander Schleicher Segelflugzeugbau Poppenhausen D-36163 Germany	Schleicher Operation Manual and Maintenance Instructions to 10/03/2008		
3b	Engine (if applicable)	N/A			
3c	Propeller (if applicable)	N/A			
Additional maintenance requirements not covered above (applicable to all AMPs, regardless of whether they are based on design approval holder (DAH) data or minimum inspection programmes (MIPs))					
4	Indicate if any of the following additional maintenance requirements are applicable (when replying 'YES', list the specific requirements in Appendix B (add to the BGA SDMP 267 EASA mandatory and BGA CAMO requirements found after task 89) to this AMP			Yes	No
	Maintenance due to specific equipment and modifications			Yes	
	Maintenance due to life-limited components			Yes	
	Maintenance due to mandatory continuing-airworthiness information (airworthiness limitations (ALIs), certification maintenance requirements (CMRs), specific requirements in the TCDS, etc.)			Yes	
	Maintenance due to repetitive ADs			Yes	
	Maintenance due to specific operational/airspace directives/requirements (altimeter, compass, transponder, etc.)				No
	Maintenance due to type of operation or operational approvals				No
5	Indicate if there is any maintenance due to specific recommendations in service bulletins, service letters, etc. (when replying 'YES', list the specific recommendations and any deviations in Appendix B to this AMP)			Yes	

Pilot-owner maintenance

6	Does the Pilot-owner perform Pilot-owner maintenance (ref. Part-M)	Yes	No
	If yes, enter the name of the pilot-owner(s): Pilot-owner name: _____ Licence Number: _____ _____ BGA Cert _____ _____ BGA 1/C/ _____ Signature: _____ Date: / /	Yes	

Approval/declaration of the maintenance programme by owner

7	Declaration by owner <i>'I hereby declare that this is the maintenance programme applicable to the aircraft referred to in Field 3, and I am fully responsible for its content and, in particular, for any deviations from the Design Approval Holder's recommendations.'</i> Signature/name/date: _____ / /
---	--

Certification statement

8	<i>'I will ensure that the aircraft is maintained in accordance with this maintenance programme and that the maintenance programme will be reviewed and updated as required.'</i> Signed by the person/organisation responsible for the continuing airworthiness of the aircraft according to M.L.A.201: Owner <input type="checkbox"/> — Lessee <input type="checkbox"/> Name of owner/lessee _____ Address: _____ Telephone/fax: _____ Email: _____ Signature/date: _____ / /
---	--

9	Appendices attached to BGA SDMP 267 — Appendix A YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> BGA SDMP 267 already complies with Appendix A requirement — Appendix B YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> Add to the BGA SDMP 267 EASA mandatory and BGA CAMO requirements found after task 89
---	--

Record of periodic reviews and revisions of the Aircraft Maintenance Programme (in accordance with M.A.302(g) or M.A.302(h)5, as applicable) (add more rows/lines if required)

10	Entire below changes to this SDMP and revision number	Date and signature of owner
	Issue 1	

Work pack file ref:	
Page No:	Total pages in workpack

Registration G-

BGA No.

Type. ASW15A

Serial No 15000

Task Item	Description	Inspection detail	Operation Insp/check initials
Tasks 1 to 62 applicable to all aircraft (delete row/line as or write N/A as required)			
Tasks 63 to 89 apply to powered sailplanes (delete row/line as or write N/A as required)			
0	All Tasks General	The aircraft must be clean. Inspect for security, damage, wear, integrity, drain/vent holes clear, signs of overheating, leaks, chafing, cleanliness and condition as appropriate to the particular task. Whilst checking GRP Composite structures check for signs of impact or pressure damage that may indicate underlying damage. The manufacturer's maintenance manual must be used for specific maintenance instructions.	
1	Fuselage Paint/Gelcoat	Inspect external surface and fairings, gel coat, fabric, metal skins and paintwork. Check that registrations marks are correctly applied. All turbulator tapes are fitted correctly and secure. Ensure compliance with Generic Requirement 8 Fabric Inspection.	
2	Fuselage structure	Check frames, formers, tubular structure, skin and attachments. Inspect for signs if corrosion on tubular framework. Wooden structure inspection ref BGA Inspection 047/02/2006.	
3	Nose Fairing	Inspect for evidence of impact with ground or objects. Inspect nose tow release unit and aperture.	
4	Rudder	Check rudder assembly, hinges, attachments, balance weights.	
5	Pot Pitot/Ventilator	Check alignment of probe, check operation of ventilator and canopy demisting.	
6	Centre section fairing	Inspect for security, damage and condition.	N/A
7	Wing attachments	Inspect the wing structural attachments. Check for damage, wear and security. Check for rigging damage. Check condition and security of wing attachment pins and associated bearings.	
8	Canopy, doors, locks, jettison	Inspect canopy/door and frame and transparencies for cracks, unacceptable distortion and discoloration. Check operation of all locks and catches. Carry out an operational test of the canopy jettison system from all positions. Canopy jam during jettison inspection ref BGA Inspection 021/10/2001. Check canopy gas strut inspection ref BGA Inspection 031/05/2002.	
9	Seat / cockpit floor	Inspect seat (s). Check that all loose cushions are correctly installed and as appropriate, energy absorbing foam cushions are fitted correctly and secured. Ensure that all seat adjusters fit and lock correctly. Seat trim inspection ref BGA Inspection 019/10/2001.	
10	Cleanliness / loose article check	Check under cockpit floor/ seat pan and in rear fuselage for debris and foreign items.	
11	Front skid/nose wheel & mounts	Inspect for evidence of hard/heavy landings. Check skid wear. Inspect wheel, tyre and wheel box. Check tyre pressure.	N/A
12	Mainwheel, tyre & brake assembly	There should be zero play (unless a tolerance is specified in the manual) in the brake torque link/stud. Check for integrity of hydraulic seals and leaks in pipe work. Check life of hydraulic hoses and components if specified by manufacturer. Remove brake drums, check brake lining wear. Check disk/drum wear. Refit drum. Check brake adjustment. CAUTION: BRAKE DUST MAY CONTAIN ASBESTOS. Check operation of brake. Check level of brake fluid and replenish if necessary. CAUTION: CHECK TYPE OF BRAKE FLUID USED AND OBSERVE SAFETY PRECAUTIONS. If DOT 3 or DOT 4 automotive brake fluid is used; change at regular intervals as it absorbs water. Tyres check for wear, sidewall damage, perishing, correct pressure and creep marks have not moved.	
13	Undercarriage suspension	Check springs, bungees, shock absorbers, and attachments. Check for signs of damage. Service strut if applicable. If rubber parts fitted check for perished rubber and bulges. Note: Carry out with weight off the landing gear.	N/A

14	Undercarriage retraction system	Check retraction mechanism and controls with aircraft on jacks/dolly, check warning system if fitted, gas struts, doors and linkages/springs, over centre/locking device. Perform retraction test.	
15	Tail skid / wheel	Inspect for evidence of hard/heavy landings. Check skid wear. Inspect wheel, tyre and wheel box. Check bond of bonded skids. Check tyre pressure.	
16	Release hooks	Inspect nose and C of G release hooks and controls as per manufacturer's instructions. Check operational life against manufacturer's instruction (both calendar life and actuations). Carry out operational test. If more than one release hook or control is fitted check operation of all release hooks from all positions.	
17	Harnesses	Inspect all harnesses for condition and wear of all fastenings, webbing and fittings. Check operation of release and adjustments. See BGA AMP manual Leaflet 4-8 for advice.	
18	Flight/rudder pedal assemblies	Inspect rudder pedal assemblies and adjusters.	
19	Rudder control circuit & stops	Inspect rudder control rods/cables. Check that control stops are contacting and secure. Pay attention to wear and security of liners and cables in "S" tubes. Check rudder assembly, hinges, attachments and balance weights are secure.	
20	Elevator control circuit & stops	With the tail-plane derigged, check tail-plane attachments, inspect elevator control rods/cables. Check that control stops are contacting and secure. Inspect self-connecting control devices, check gel coat, fabric covering or metal skin.	
21	Aileron and flap control circuit & stops	Inspect aileron control rods/cables. Check that control stops are contacting and secure. Inspect self-connecting control devices.	
22	Flap control circuit and detents	Inspect flap control circuit, check any gas struts fitted work as specified. Check that all detents and springs in the flap circuit and handle operate correctly as specified by Manufacture and detents are not too excessively worn.	N/A
23	Trimmer control circuit	Inspect trimmer control rods/cables. Check friction/locking/connecting devices.	
24	Air brake control circuit	Inspect air brake control rods/cables/bellcranks/bracket. Check friction/locking device (if fitted). Inspect self-connecting control devices.	
25	Wheel brake control circuit	Inspect wheel brake control rods/cables. If combined with air brake, ensure correct rigging relationship and you can still achieve full airbrake. Check parking brake operation (if fitted).	
26	Instrument panel assemblies	Inspect instrument panel and all instruments/equipment. Check that instrument readings are consistent with ambient conditions. Check marking of all switches, circuit breakers and fuses are correctly labelled. Registration is displayed on instrument panel. Check operation of all installed equipment as possible i.a.w. manufacturer's instructions. Check all instruments are marked as required by Flight Manual.	
27	Pitot/static system	Inspect pitot probes, static ports all tubing (as accessible) for security, damage, cleanliness, kinking and condition. Drain any water from condensate drains. Perform system leak check.	
28	ASI operational check	Carry out accuracy of the airspeed indicator (in situ permissible) i.a.w. manufacturer's instructions (use manufacturer's limits. If Not avail. Max error 2 knots). Ensure colour coding has been applied if required in flight manual.	
29	Altimeter datum	Check barometric sub scale. (max. error 2 Mb).	
30	Electrical installation/fuses/trips	Check all electrical wiring for condition. Check for signs of overheating and poor connections. Check fuses/trips for condition and correct rating.	
31	Battery	Check battery mounting for security and operation of clamp. Check for evidence of electrolyte spillage and corrosion. Check that battery has the correct main fuse fitted. It is recommended to carry out battery capacity test on gliders equipped with radio, used for cross-country, airways or competition flying. Note: In accordance with equipment manufacturer's recommendations where capacity checks are recommended by the equipment manufacturer. See BGA AMP manual leaflet 4-9.	
32	Oxygen systems	Inspect oxygen system. Check bottle hydrostatic test date expiry i.a.w. manufacturer's recommendations. Ensure that bottle is not completely empty (200psi min) refill with aviator's oxygen only. Clean masks and regulators with approved cleaning wipes. Ensure that oxygen installation is recorded on weight and C of G schedule. Check all instruments are marked as required by Flight Manual. CAUTION: OBSERVE ALL SAFETY PRECAUTIONS	N/A
33	Radio installations and placards, transponders	Check radio installation, microphones, speakers and intercom if fitted. Check that call sign placard is installed. Check aircraft registration placard is visible near radio. Carry out radio ground function test. Record type fitted. All avionics (including transponders) to be maintained as per the manufacturer's instructions and applicable ADs.	
34	Radio frequency check	48-month frequency tolerance check. (Not required for modern 720/760 or later channel transceivers)	N/A
35	Removable ballast	Check removable ballast mountings and securing devices for condition. Check that ballast weights are painted a conspicuous colour. Check that provision is made for the ballast on the loading placard. Check that the ballast arrangements as configured are supported by the Flight Manual (technical notes often require flight manual amendments).	N/A

36	Colour coding of controls	Ensure that controls are colour coded and in good condition, as follows; Tow release: Yellow Air Brakes: Blue Trimmer: Green Canopy normal operation: White Canopy jettison: Red Combined Canopy jettison and normal operation: White and Red Other controls: clearly marked but not using any of the above colours.	
37	Equipment stowed in centre section	Check for security and condition. Check validity of any safety equipment. Check manufacturer's and NAA (if required) data plates.	
38	Wing struts/wires	Inspect struts for damage and internal corrosion. Re-inhibit struts internally every 3 years or in accordance with manufacturer's instructions.	N/A
39	Drag chutes & controls	Check for correct operation. Inspect chute, rigging lines, packing and release mechanism. Check repackaging date.	N/A
40	Water ballast system	Check water ballast system, wing and tail tanks as fitted. Check filling points, level indicators, vents, dump and frost drains for operation and leakage. If loose bladders are used check for leakage and expiry date as applicable. Ensure outside temp gauge is fitted and reads ambient temperature.	N/A
41	Tail plane and elevator	With tail plane de-rigged check tail plane and attachments, self-connecting and manual control connections, check condition of gel coat, fabric or metal skin. All turbulator tapes are fitted correctly and in secure. Check condition and fitment of sealing tape ref BGA Inspection 009/10/2000. Control tape and Mylar seal inspection ref BGA Inspection 011/12/2000. Wooden structure inspection ref BGA Inspection 047/02/2006.	
42	Left wing	Check mainplane structure externally and internally as far as possible. All vents and drain holes are clear. Check gel coat or fabric covering. Check registration marks are correctly applied. Ensure all boundary layer blow holes are not blocked and pressure feed system for them is serviceable. All turbulator tapes are fitted correctly and secure. Ensure compliance with Generic Requirement 8, Fabric Inspection. Wooden structure inspection ref BGA Inspection 047/02/2006.	
43	Left wing controls	Inspect aileron and flaperon assemblies, hinges, control connections, springs/bungees, tapes and seals. Ensure that seals do not impair full range of movement. Control tape and Mylar seal inspection ref BGA Inspection 011/12/2000.	
44	Left air brake/spoiler	Inspect air brake/spoiler panel(s) operating rods, closure springs, and friction devices as fitted. Check locking forces if specified by manufacturer or AD.	
45	Left Flap	Check flap system and control. Inspect self-connecting control devices.	N/A
46	Right wing	Check main plane structure externally and internally as far as possible. All vents and drain holes are clear. Check gel coat or fabric covering. Check registration marks are correctly applied. Ensure all boundary layer blow holes are not blocked and pressure feed system for them is serviceable. All turbulator tapes are fitted correctly and secure. Ensure compliance with Generic Requirement 8, Fabric Inspection. Wooden structure inspection ref BGA Inspection 047/02/2006 (5 year repeat).	
47	Right wing controls	Inspect aileron and flaperon assemblies, hinges, control connections, springs/bungees, tapes and seals. Ensure that seals do not impair full range of movement. Control tape and Mylar seal inspection ref BGA Inspection 011/12/2000.	
48	Right air brake/spoiler	Inspect air brake/spoiler panel(s) operating rods, closure springs, and friction devices as fitted. Check locking forces as specified by AMM or AD	
49	Right Flap	Check flap system and control. Inspect self-connecting control devices.	N/A
50	Bonding/vents/drain	Check all bonding leads & straps. Check all vents and drains are clear from debris.	
51	Lubrication	Lubricate and replenish fluids in accordance with manufacturer's requirements	
52	Markings	Check side and under-wing markings are correct. If applicable, an exemption for alternate display is approved. Ident plate for CAA registered aircraft present. Identification plate for National Aviation Authority registered aircraft is present. Other identification markings in accordance with local (national) rules. BGA Number on fuselage for BGA registered aircraft.	
53	Mandatory checks	Check for compliance of all mandatory modifications, airworthiness directives and inspections applicable to the airframe, accessories & equipment. Record compliance in the logbook. State of design Type Certificate and STC holder AD list, BGA Compendium, BGA Technical News Sheet, BGA Mandatory inspections, manufacturer's mandatory check list (if available).	
54	Manufacturer's recommendation and life inspections	Review manufacturer's maintenance schedules and instructions for continued airworthiness for the airframe to establish if any additional work, servicing or preservation action is required. Any Deviations from TCDS holder's recommendations must be recorded and signed for by the owner.	
55	Control deflections & free play	Check and record range of movements and cable tensions (if specified), check free play.	
56	Duplicate inspections	Record each item requiring a duplicate inspection on an additional worksheet and complete prior to releasing aircraft back to service.	

57	Weighing	Review weighing record to establish accuracy against installed equipment. Check date of last weighing (BGA Maximum deviation period for re-weigh is 8 years or after painting). See Generic Requirement 10 and BGA AMP. However, between 8 year cycles, the C of G must be calculated in accordance with Part NCO. For EL1 aircraft the mass and centre of gravity (CG) position should be revised whenever the cumulative changes to the dry operating mass exceed $\pm 0.5\%$ of the maximum landing mass or, for aeroplanes, the cumulative change in CG position exceeds 0.5 % of the mean aerodynamic chord. This may be done by weighing the aircraft or by calculation. If the AFM requires to record changes to mass and CG position below these thresholds, or to record changes in any case, and make them known to the pilot-in-command, mass and CG position should be revised accordingly and made known to the pilot-in-command.	
58	Speed/weight/manoeuvre placard	Check placard is correct and legible and accurately reflects the status of the aircraft.	
59	Hours	Hours at this inspection. hours	
60	Launches	Launches at this inspection. Launches	
61	Modifications	Review Log Book and verify that any modifications incorporated since last Airworthiness Certificate or ARC renewal have been approved and correctly embodied and recorded.	
62	Log book	Complete log book entry. Ensure that all flying records are entered and up to date.	
63	Flight Manual	Verify that the Aircraft Flight Manual or Operating Handbook is at the latest revision.	
Tasks 63 to 89 are only applicable to Powered Sailplanes			
64	Engine pylons & mountings & flexible vibration dampers and starter motor (if fitted)	Inspect engine and pylon installation. Check engine compartment and fire sealing. Check pylon for cracks and delamination if made from composites. Ensure all rubber parts (especially engine mounts) are not perished, cracked or deteriorated. Check starter motor security, casing, wiring, condition of drive gear and flywheel if fitted.	N/A
65	Gas strut	Check gas strut with AMM.	N/A
66	Pylon/engine stops	Check limit stops on retractable pylons. Check restraint cables.	N/A
67	Electric actuator	Inspect electric actuator, motor, spindle drive and mountings.	N/A
68	Electrical wiring, external and internal lights/strobes/beacons	Inspect all electrical wiring. Pay special attention to wiring that is subject to bending during extension and retraction of engine/pylon. Check function of all lights.	N/A
69	Limit switches	Check operation of all limit switches & strike plates. Ensure not damaged by impact.	N/A
70	Fuel tank	Check fuel tank mountings, electrical bonding and tank integrity. Check fuel quantity indication system if fitted. If a GRP tank is fitted ensure the integrity of the internal resin in case it has been affected by ethanol and other contaminants contained in certain fuels. Filling nozzle receptacle correctly labelled	N/A
71	Fuel pipes & vents	Check all fuel pipes especially those that are subject to bending during extension and retraction of engine/pylon. Check vents clear. Ensure overboard drains do not drain into engine compartment. Check self-sealing couplings. Ensure all swaged fittings, jubilee clips are secure and there is no perishing.	N/A
72	Fuel cock or SOV	Check operation of fuel cock or shut off valve & indications.	N/A
73	Fuel pumps and filters	Clean or replace filters as recommended by manufacturer Check operation of fuel pumps for engine supply or tank replenishment. Check fuel pump controls and indications.	
74	Decompression valve	Inspect decompression valve and operating control.	N/A
75	Spark plugs	Carry out spark plug service. It is recommended to replace spark plugs at annual intervals.	N/A
76	Harnesses & magneto	Inspect low tension and high-tension wiring, connectors, spark plug caps. Check magneto to engine timing. Check impulse coupling operation.	N/A
77	Propeller	Inspect propeller, hub, prop bolts torque (if require) folding mechanism, brake, pitch change mechanism, stow sensors, belts and pulleys condition and tension. Lubricate all as required by TCDS holder. Check overhaul period and TBO of propeller.	N/A
78	Doors	Check engine compartment doors, operating cables, rods and cams.	N/A
79	Safety springs	Check all safety and counterbalance springs.	N/A
80	Extension and retraction	Check extension and retraction operation times are within limits specified by manufacturer. Check light indications and interlocks for correct operation. Check for factory software updates every year.	N/A
81	Exhaust, turbocharger, cabin and carburettor heat.	Inspect exhaust system, silencer, shock mounts and links. Pressure test cabin and carb heater exhaust heat exchanger (if applicable). Check turbocharger as required by TCDS holder. See CAA CAP 562 CAAIP Leaflet B-190 for further guidance	N/A
82	Engine installation	Inspect engine and all accessories. Carry out compression test and record results on worksheet.	N/A
83	Lubrication	Change engine oil and filter (cut filter open and check gauze for contamination and metal). Replenish oil and additive tanks.	N/A

84	Engine instruments and controls	Inspect all engine instruments and controls. Check control unit, mounts, bonding and connections. Carry out internal self-test if fitted. Check engine and propeller controls for full and free movement – throttle, mixture, carburettor heat, cowl flaps and propeller pitch.	N/A
85	Engine battery	(if separate to airframe battery) Inspect battery and mountings. If main fuse is fitted check rating and condition. Carry out capacity test, refer to AMM I for guidance.	N/A
86	Placards	Check all placards in accordance with Flight/Maintenance Manual and are legible.	N/A
87	Oil and fuel leaks	Perform ground run (except with dive start engines). Check temperatures and pressures and indication within permitted range. With the engine fully serviced (and ideally still warm from a check run) check the fuel and oil system for leaks.	N/A
88	Mandatory checks	Check for compliance of all mandatory modifications, Airworthiness Directives and inspections applicable to the engine, propeller, accessories & equipment. Record compliance in the logbook. TCDS holder AD list, EASA AD list, Equipment ADs (including Technical notes and Service Bulletins) BGA Compendium, BGA Technical News Sheet, BGA Mandatory Inspections, BGA Compendium, in service issues, manufacturer's mandatory check list (if available) and factory service bulletins and technical notes.	N/A
89	Manufacturer's recommendation	Review manufacturer's maintenance schedules and instructions for continued airworthiness for the engine/propeller to establish if any additional work is required. All recommendations not carried out require an owner declared deviation.	N/A

EASA Mandatory items. Add ALLs (found in section 4 of modern AMM and TCDS), only add EASA and State of Design ADs that are recurring (add more rows/lines if required)			
LTA 93-001-3 TN 25	Locking of L'Hotellier ball and socket connectors		
AD 81-91 TN 27	Increase of service life – Inspection due at 3,000 flying hours		
LBA AD1994-224/02	TOST hook condition and life (mandatory 10,000 actuations and recommended 4 year life)		
AD82-216	Nicopress sleeves inspection after cable replacement		
BGA CAMO requirements (found in Compendium and BGA inspections) and if desired add advisory Maintenance Manual recommendations (if embodied and not already included in the SDMP 267) add more rows/lines below if required. You can also add other maintenance you want to include on this form. For instance, Flarm software updates or reminders from the Maintenance Manual.			
TNS 02/05	Inspection of seat harness		
BGA Mandatory Inspection 056-08	Check security of stick and airbrake grips as required by AAIB recommendation at annual		
BGA Mandatory Inspection 011-12-2000 iss1 TNS 5-2010 TNS 06/99	Flying control surface tape and seals must be in good condition – also TNS 5-2010		
BGA Compendium TNS 02/87 TNS 06/99 TNS 5-2010	Reweigh at least every 8 years or after repaint/refinish or significant modifications and installation of additional equipment		
BGA Compendium	Update Flarm and airspace software		
TNS 12/00	Ballast weights must be secured		
TNS 12/03	Check for wear at slipping cables at rudder cable S tubes. Worn anti-wear liners must be replaced. Check for wear into tubes if liners are damaged		
TNS 08/00	Assess the need for end-to-end cable inspections at annual check		
TNS 2-2010	Severe corrosion of control cables – inspect in moisture traps, ducted cables etc.		
TNS 5-2012	Check for poorly formed cable swaging		
TNS 2-2014	Check for incorrect routing of cables over pulleys, incorrect make up of cables, incorrect adjustment		
TNS 08/02	Dynafoam seat cushions – check for thickness and condition		

TNS 10/04	Secondary damage when inspecting GRP structures that may be difficult to spot if aircraft is finished in acrylic paint	
TNS 04/05	If battery current limiters are installed, check fuses are also fitted	
TNS 4-2014	Check for correct rating on fuses and check wiring to avoid chafing	
TNS 1-2007	Check for legibility of all placards and replace if necessary ref ENG NEWS 30	
TNS 3-2006 TNS 4-2006	Check only stainless steel or Inconel locking wire has been used as required, except for tell tails where fuse wire is used	
TNS 5-2009	Record serial numbers of components when changed	
TNS 1-2010	Check for correctly locked turnbuckles ref EASA SIB 2010-06	
TNS 4-2014	Check and inspect control grips iaw fitting guidance	
	Schleicher Technical Notes (TN's)	
	None Found Applicable to the ASW15 Glider	
	ASW15 In service reports Advisory:	
06/75	Tow release cable – damaged in conduit	
08/83 & 08/93	Undercarriage handle knob detached due to locking pin failed	
10/97	Ailerons oscillate if too out of balance	
04/03	Tailplane mountings – loose bolts in ply reinforcement	
4-2011	Incorrect rivets used causing collapse in landing gear	

<p>Add any Deviations from TCDS holder and equipment manufacturer recommendations from mandatory service bulletins, AMM, AFM and TCDS. The BGA requires justification and Acceptable Means of Compliance for Deviations. No deviations are permitted from Airworthiness Directives or mandatory maintenance (ALIs) or BGA CAMO requirements as specified in the Maintenance/Flight Manuals, TDCS, ADs and BGA Compendium (add more rows/lines if required)</p>			<p>Owner must sign & date & below</p>
Service/life/TBO Interval		Task Description	
TC holder recommendations (hrs/cycles/calendar)	Changed to		
12 Years	Annual Review	Gadringer Harness Life	<p>Engineering justification and alternative means of compliance (AMC). Add extra documents to this MIP section as required to support AMC and engineering justification of a deviation.</p> <p>Harness life extended from 12 years to annual review subject to annual inspection using BGA AMP 4-8 guidelines. Within the BGA CAMO strict adherence to BGA AMP 4-8 guidelines has shown seat harnesses have been safely extended with no loss/perceivable loss of serviceability Ref TNS 1-2007 See on condition criteria in TNS 5-2013</p>

4 Years	8 Years	Reweigh interval Page 32 AMM	Reweigh interval extended from 4 years to 8 years unless anything happens to change the weight or C of G. While in the BGA CAMO history has shown there has been no change to safety by extending the reweigh period to 8 years Owners	
4 Years	Annual Review	TOST 4 year recommended replacement/overhaul of release hooks	History has shown that subject to annual maintenance and lubrication (IAW TOST hook maintenance procedures) that service life is unaffected extending the 4 year recommendation.	

General Remarks

Date of ARC or BGA C of A expiry:
Other remarks:

Record identifying marks.	Fin:	Fuselage: G-	Under wing: G-
---------------------------	------	--------------	----------------

Certificate of Release to Service

All work has been recorded in the appropriate logbook and all additional worksheets have accounted for and certified and for BGA registered gliders.

EASA Aircraft - Certifies that the work specified, except as otherwise specified, was carried out in accordance with Part-M and in that respect is considered ready for release to service. BGA Approval No. UK.MF.0007.

(* Written signature required)

Inspector Name: _____ Signed _____ Date: _____ BGA Inspector No: _____